





Note that all unique customer requirements (i.e tolerance) need to be verified thru Alfa Laval.



HEATING SURFACE m²
NETWEIGHT 11.3 kg
OPERATING WEIGHT kg
PLATE MATERIAL ALLOY 316
PLATE GROUPING 1*24H/1*25H

Frameplate is depressed 2.1 mm
at connections S3 and S4 if holed.
Pressureplate is depressed 2.1 mm
at connections T3 and T4 if holed.

T1 T2 T3 T4 locations on back side
correspond to S1 S2 S3 S4 on front side

ALL DIMENSIONS IN MILLIMETERS

SIDE	MEDIA	INLET	TEMP.	OUTLET	TEMP.	FLOW RATE	PRESSURE DROP	LIQUID VOL.
1	Water	T1	°C	T2	°C	kg/h	kPa	2.6 dm ³
2	Water	S3	°C	S4	°C	kg/h	kPa	2.5 dm ³

PRESSURE VESSEL APPROVAL
CB60-50H-F (3287161433)

PED

www.alfalaval.com

CUSTOMER NAME / REF. NO.

TOTAL LENGTH 190 mm
TOTAL WIDTH 113 mm
TOTAL HEIGHT 527 mm

COMPANY / REF.
EKO ELEKTROPRIGODNO DOO BEOGRAD